# ProLite B2209HDSD-1

This attractive, slim bezel 22" LCD display features double input configuration of DVI and Analogue for ensured compatibility. The B2209HDSD continues the trend of true 1920 x 1080, 16:9 format panels in desktop displays. Featuring an incredible 2msec response time and 20,000:1 Advanced Contrast Ratio the expierience for gamers is enhanced and depth of colour in Video assured. ProLite B2209HDSD is height adjustable and features PIVOT function

| | |
|---|---|
| Panel | TN |
| Diagonal | 22" |
| Display area h x w | 268.6 x 447.5 mm; 10.6" x 18.8" |
| Response time | 2 ms |
| Contrast | 20 000 : 1 ACR |
| Contrast | 1000 : 1 typical |
| Brightness | 300 cd/m² typical |
| Viewing zone | horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.248 x 0.248 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 24 - 80 KHz |
| Vertical sync | 55 - 75 Hz |
| Analog input connector | D-Sub |
| Digital input connector | DVI-D |
| HDCP | yes |
| Output connector | headphone connector |
| Synchronization | Separate Sync |
| Plug & Play | VESA DDC2B™ |
| Speakers | 2 x 2 W (Stereo) |
| Included accessories | power Cable, D-Sub Cable, DVI-D Cable, Audio cable, stand-base, screw for stand fixing, quick start guide, safety guide |
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Controls | Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu /Select Button, + /Volume Button (+), - / Eco Button (-), Auto) |
| User controls | luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (gamma, colour temperature), OSD setup (H. position, V. position, timeout, language), others (reset, signal select, information), volume, auto adjust |
| Driver | Windows 95 / 98 / 2000 / ME / XP / Vista / 7 |
| Ergonomics | CE, TÜV-GS, TCO '03 |
| Power supply | AC 100 - 240 V, 50 / 60 Hz |
| Power Supply Unit | internal |
| Power usage | 41 W typical; max. 1 W in Power management mode |
| Power management | VESA DPMS, ENERGY STAR® |
| Anti-theft-device | Kensington-lock™ prepared |
| VESA mounting | 100 mm |
| Height adjustment | 110 mm |
| Rotation (pivot function) | 90° |
| Swivel Stand | 340°; 170° left; 170° right |
| Tilt angle | 20° up |
| Dimensions w x h x d | 513 x 399.5 (509.5) x 249.5 mm |
| Weight | 6.3 kg |
| Aspect ratio | 16 : 9 |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.